

WELLHEAD LUBRICATION / GREASE FITTING



MODEL CODE : EGF

SPECIAL FEATURES

- Sizes available 1/2"NPT , 9/16" Autoclave in MOC Carbon Steel and SS316L
- Available in 10000 PSI,15000 PSI and 20000 PSI pressure ratings
- Floating cone with packing prevents galling across seat and leakages through threads
- Max Operating temperature up to 200 deg. centigrade
- Protective caps are provided for ingress protection
- Optionally available with NACE MR-01-75 compliance

APPLICATIONS

- Oil and Gas Industry
- Petrochemical industries
- Refineries and Chemical Industries
- Packing Injection Systems
- Lubrication / Sealant Applications

DESCRIPTION

These fittings are machined from bar stock with sturdy design and most durable sealant fitting. High quality materials and stringent quality control checks provides longer life and better performance in the field. Screwed vented cap protects the button head flange and mating threads from corrosion and damage. These lubrication fittings are available in different thread sizes and types to meet mounting requirements and service conditions.

TESTING

Every fitting is hydrostatically tested on water at 1.5 times of rated pressure.



20000 PSI UNF THREAD



10000 PSI 1/2" NPT



HOW TO ORDER

BASIC MODEL

CODE

SIZE

8 1/2" 9 9/16"

MOC

CS CARBON STEEL M MONEL 400

SS SS316L

THREADS

N NPT

A AUTOCLAVE

PRESSURE RATING

10 10000 PSI

15 15000 PSI

20 20000 PSI

Example

EGF

X

X

X

XX

Ordering Example : EGF - X - X - X - XX

Modifications may take place and materials specified may be replaced by others without prior notice due to continuous developments.

Note: Specifications and dimensions given in this product catalogue represent the state of engineering at the time of printing.

Modifications may take place and materials specified may be replaced by others without prior notice.